## **MULE PRO-DXT™ EPS DIESEL**









## **POWER**

**Engine** 4-stroke, 3-cylinder, OHV, liquid-cooled, diesel

Displacement 993cc

**Bore x Stroke** 2.91x3.03 in

**Compression Ratio** 23.5:1

**Maximum Torque** 38.3 lb-ft @ 2400 rpm

**Fuel System** Bosch in-line injection pump

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

**Final Drive** Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

**Engine Braking** Yes

**Alternator Output** 

(max)

55 amp

## CAPABILITY

Front Suspension / Wheel Travel

Double wishbone/8.7 in

Rear Suspension /

Wheel Travel

Double wishbone/8.5 (L) /8.7 (R) in

Front Tires 26x9 00-12

**Rear Tires** 26x11.00-12

**Park Brake Type** 

Independent, Mechanical Disc

Steering

Electric Power Steering (EPS), Tilt steering

**Front Brakes** 

Dual Disc, 2 piston caliper

Rear Brakes

Dual Disc, 1 piston caliper

**Ground Clearance** 10.2 in

**Fuel Capacity** 7.9 gal

**Turning Radius** 16.0 ft

Cargo Bed 42.7 x 53.7 x 11.0 in (3-person), 22.0 x 53.7 x 11.0 in (6-Dimensions (LxWxH)

person)

**Cargo Bed Capacity** 999 lb (3-person), 350 lb (6-person)

**Load Capacity** 

**Seating Capacity** 3-person (1 row), 6 person (2 row)

**Towing Capacity** 

Lighting (2) Halogen headlights.

## **DETAILS**

**Overall Length** 133.3 in

**Overall Width** 64.0 in

**Overall Height** 77.6 in

**Curb Weight** 1936.0 lb\*

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters,

2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, glow plug indicator, CVT and EPS warning indicators, neutral, reverse and parking

indicators, seatbelt reminder lamps

**Wheel Type** Steel

**Color Choices Timberline Green** 

Kawasaki Strong 3-Year Limited Warranty Warranty

12, 24, or 36 months **Kawasaki Protection** Plus™ (optional)

<sup>\*</sup>Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.



