







PUWER		
Engine	4-stroke, 4-cylinder, DOHC, 16-valve, liquid- cooled	
Displacement	948cc	
Bore x Stroke	73.4 x 56.0mm	
Compression Ratio	10.8:1	
Fuel System	DFI® with Keihin 36mm throttle bodies	
Ignition	TCBI with electronic advance	
Transmission	6-speed, return shift	
Final Drive	Sealed chain	
Maximum Torque	72.3 lb-ft @ 6,500 rpm	

Front Brakes	Dual 300mm discs with four-piston calipers, ABS
Rear Brakes	Single 250mm disc with single-piston caliper, ABS

	ABS
DETAILS	
Frame Type	Trellis, high tensile steel
Rake/Trail	25.0°/3.9 in
Overall Length	83.1 in
Overall Width	34.1 in
Overall Height	46.5 in
Ground Clearance	5.1 in
Seat Height	32.9 in
Curb Weight	474.1 lb (50-State Model)*

PERFORMANCE

Rear Tire

Front Suspension / Wheel Travel	Inverted telescopic fork with (13-way) adjustable compression and rebound (11-way) damping, spring preload (15-turn)/4.7
Rear Suspension / Wheel Travel	Horizontal back-link swingarm with stepless adjustable rebound damping and spring preload/5.5 in
Front Tire	120/70 ZR17

180/55 ZR17

Wheelbase 57.9 in

Color Choices Metallic Diablo Black

Warranty 12 Month Limited Warranty

Kawasaki 12, 24, 36 or 48 months

Protection

4.5 gal

Fuel Capacity

Plus™ (optional)

^{*}Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.



