PNWFR

Wheel Travel

Suspension /

Wheel Travel

Front Tire

Rear Tire

Rear









PUWER		
Engine	4-stroke single, SOHC, air-cooled	
Displacement	144cc	
Bore x Stroke	58.0 x 54.4mm	
Compression Ratio	9.5:1	
Fuel System	20mm Keihin carburetor	
Ignition	Digital DC-CDI	
Transmission	5-speed, return shift, with wet multi-disc manual clutch	
Final Drive	Chain	

DETAILS	
Rear Brakes	Single 186mm petal disc with single-piston caliper
Front Brakes	Single 220mm petal disc with a dual-piston caliper

•		
Bore x Stroke	58.0 x 54.4mm	
Compression Ratio	9.5:1	
Fuel System	20mm Keihin carburetor	
Ignition	Digital DC-CDI	
Transmission	5-speed, return shift, with wet multi-disc manual clutch	
Final Drive	Chain	
PERFORMANCE		
Front Suspension /	33mm telescopic fork/7.1 in	

DETAILS		
Frame Type	High-tensile steel, box-section perimeter	
Rake/Trail	27° /3.3 in	
Overall Length	71.7 in	
Overall Width	31.1 in	
Overall Height	41.3 in	
Ground Clearance	9.3 in	
Seat Height	30.7 in	
Curb Weight	205.0 lb*	
Fuel Capacity	1.5 gal	
Wheelbase	49.6 in	
Color Choices	Lime Green	
Warranty	6 Months	
Kawasaki Protection Plus™ (optional)	12, 24, or 36 months	

^{*}Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

Uni-Trak® linkage system and single shock

with 5-way preload adjustability/7.1 in

70/100-17

90/100-14



