

2023

# KLX<sup>®</sup>140R L

**RYMCO**  
POWERSPORTS

  
**Kawasaki**  
 Let the good times roll<sup>®</sup>


 LIME GREEN


## POWER

<b>Engine</b>	4-stroke single, SOHC, air-cooled
<b>Displacement</b>	144cc
<b>Bore x Stroke</b>	58.0 x 54.4mm
<b>Compression Ratio</b>	9.5:1
<b>Fuel System</b>	20mm Keihin carburetor
<b>Ignition</b>	Digital DC-CDI
<b>Transmission</b>	5-speed, return shift, with wet multi-disc manual clutch
<b>Final Drive</b>	Chain

**Front Brakes**

Single 220mm petal disc with a dual-piston caliper

**Rear Brakes**

Single 186mm petal disc with single-piston caliper

## DETAILS

<b>Frame Type</b>	High-tensile steel, box-section perimeter
<b>Rake/Trail</b>	27° / 3.8 in
<b>Overall Length</b>	74.6 in
<b>Overall Width</b>	31.1 in
<b>Overall Height</b>	42.3 in
<b>Ground Clearance</b>	10.0 in
<b>Seat Height</b>	31.5 in
<b>Curb Weight</b>	209.4 lb*
<b>Fuel Capacity</b>	1.5 gal
<b>Wheelbase</b>	50.6 in
<b>Color Choices</b>	Lime Green
<b>Warranty</b>	6 Months
<b>Kawasaki Protection Plus<sup>™</sup> (optional)</b>	12, 24, or 36 months

## PERFORMANCE

<b>Front Suspension / Wheel Travel</b>	33mm telescopic fork/7.1 in
<b>Rear Suspension / Wheel Travel</b>	Uni-Trak <sup>®</sup> linkage system and single shock with piggyback reservoir, fully adjustable preload and 22-way rebound damping/7.1 in
<b>Front Tire</b>	70/100-19
<b>Rear Tire</b>	90/100-16

\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2022 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [Kawasaki.com](http://Kawasaki.com) for full product details.

