

2023 MULE™ 4000

RYMCO
POWERSPORTS

Kawasaki
Let the good times roll®



POWER

Engine	4-stroke, 2-cylinder, OHV 90° V Liquid-cooled
Displacement	617cc
Bore x Stroke	2.99x2.68 in
Compression Ratio	10:3:1
Maximum Torque	34.7 lb-ft @ 2500 rpm
Fuel System	DFI® with 34mm Mikuni throttle body
Transmission	Continuously Variable Transmission (CVT) with (H,N,R)
Final Drive	2WD, shaft. Dual mode rear differential with differential lock
Engine Braking	No
Alternator Output (max)	23 amp

CAPABILITY

Front Suspension / Wheel Travel	MacPherson Strut/3.9 in
Rear Suspension / Wheel Travel	DeDion Axle/2.8 in
Front Tires	23x11.00-10
Rear Tires	23x11.00-10
Park Brake Type	Independent, Mechanical Drum
Steering	Rack-and-pinion
Front Brakes	Drum
Rear Brakes	Drum

Ground Clearance	7.5 in
Fuel Capacity	6.3 gal
Turning Radius	11.0 ft
Cargo Bed Dimensions (LxWxH)	46.3 x 51.6 x 11.4 in
Cargo Bed Capacity	800 lb
Load Capacity	1327 lb
Seating Capacity	2
Towing Capacity	1200 lb
Lighting	(2) Halogen headlights (2) tail/brake lights

DETAILS

Overall Length	116.7 in
Overall Width	62.0 in
Overall Height	75.8 in
Curb Weight	1338.4 lb*
Wheelbase	73.6 in
Instruments	Parking brake warning light, coolant temperature warning light, 12V DC outlet, fuel gauge, hour meter
Wheel Type	Steel
Color Choices	Dark Royal Red
Warranty	Kawasaki Strong 3-Year Limited Warranty
Kawasaki Protection Plus™ (optional)	12, 24 or 36 months

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2022 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit Kawasaki.com for full product details.

1599