
## **MULE PRO-FXT™ EPS**











P	N	IV	N	F	R

Engine 4-stroke, 3-cylinder, DOHC, liquid-cooled, gas

812cc Displacement

**Bore x Stroke** 2.83x2.62 in

**Compression Ratio** 9.5:1

**Maximum Torque** 

DFI® with 34mm throttle body **Fuel System** 

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

**Final Drive** Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

**Engine Braking** Yes

**Alternator Output** 

(max)

48.0 lb-ft @ 3500 rpm

75 amp

## CAPABILITY

Front Suspension / Wheel Travel

Double wishbone/8.7 in

Rear Suspension / Wheel Travel

Double wishbone/8.5 (L) /8.7 (R) in

26x9.00-12, radial

**Rear Tires Park Brake Type** 

**Front Tires** 

26x11.00-12, radial

Steering

Electric Power Steering (EPS), Tilt steering

**Front Brakes** 

Independent, Mechanical Disc

Rear Brakes

Dual Disc, 2 piston caliper Dual Disc, 1 piston caliper

**Ground Clearance** 

10.2 in

**Fuel Capacity** 7.9 gal **Turning Radius** 16.0 ft

Cargo Bed **Dimensions (LxWxH)** 

42.7 x 53.7 x 11.0 in (3-person), 22.0 x 53.7 x 11.0 in (6-

**Cargo Bed Capacity** 

999 lb (3-person), 350 lb (6-person), (348 lb for California

models)

**Load Capacity** 

1616.3 lb (1263.5 for California models)

**Seating Capacity** 

3-person (1 row), 6 person (2 row)

**Towing Capacity** 

2000 lb

Lighting

(2) Halogen headlights

## **DETAILS**

**Overall Length** 133.3 in **Overall Width** 64.0 in **Overall Height** 77.6 in **Curb Weight** 1911.7 lb\*

Wheelbase

92.3 in

Instruments

Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning

indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt reminder lamps

Kawasaki Strong 3-Year Limited Warranty

Wheel Type Steel

**Color Choices** Timberline Green, Bright White

Warranty

**Kawasaki Protection** Plus™ (optional)

12, 24 or 36 months

<sup>\*</sup>Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.



