

2023

MULE SX™ 4x4 FI

RYMCO
POWERSPORTS

Kawasaki
Let the good times roll®



- TIMBERLINE GREEN
- DARK ROYAL RED



POWER

Engine	4-stroke, single-cylinder, OHV, air-cooled
Displacement	401cc
Bore x Stroke	3.23x2.99 in
Compression Ratio	8.6:1
Maximum Torque	21.4 lb-ft @ 2400 rpm
Fuel System	Fuel Injection
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)
Final Drive	Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock
Engine Braking	No
Alternator Output (max)	22.9 amp

Ground Clearance	6.7 in
Fuel Capacity	4.2 gal
Turning Radius	10.8 ft
Cargo Bed Dimensions (LxWxH)	35.6 x 40.9 x 9.6 in
Cargo Bed Capacity	399 lb
Load Capacity	915 lb
Seating Capacity	2
Towing Capacity	1100 lb**
Lighting	(2) Halogen headlights, tail/brake lights

CAPABILITY

Front Suspension / Wheel Travel	MacPherson Strut/3.1 in
Rear Suspension / Wheel Travel	Unit Swingarm/3.1 in
Front Tires	24x9.00-10
Rear Tires	24x11.00-10
Park Brake Type	Independent, Mechanical Drum
Steering	Rack-and-pinion
Front Brakes	Drum
Rear Brakes	Drum

DETAILS

Overall Length	106.7 in
Overall Width	52.6 in
Overall Height	70.9 in
Curb Weight	1031.9 lb*
Wheelbase	70.1 in
Instruments	Fuel gauge, hour meter, oil temp light, parking brake light / horn (SE only)
Wheel Type	Steel
Color Choices	Timberline Green, Dark Royal Red
Warranty	Kawasaki Strong 3-Year Limited Warranty
Kawasaki Protection Plus™ (optional)	12, 24 or 36 months

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.
 KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2022 Kawasaki Motors Corp., U.S.A.
 Specifications subject to change. Visit Kawasaki.com for full product details.