

2023

# MULE SX™ 4x4 XC LE FI

**RYMCO**  
POWERSPORTS

**Kawasaki**  
Let the good times roll®



 METALLIC ONYX BLACK



## POWER

Engine	4-stroke, single-cylinder, OHV, air-cooled
Displacement	401cc
Bore x Stroke	3.23x2.99 in
Compression Ratio	8.6:1
Maximum Torque	21.4 lb-ft @ 2400 rpm
Fuel System	Fuel injection
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)
Final Drive	Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock
Engine Braking	No
Alternator Output (max)	22.9 amp

Ground Clearance	8.1 in
Fuel Capacity	4.2 gal
Turning Radius	11.8 ft
Cargo Bed Dimensions (LxWxH)	35.6 x 40.9 x 9.6 in
Cargo Bed Capacity	399 lb
Load Capacity	884 lb
Seating Capacity	2
Towing Capacity	1100 lb**
Lighting	(4) LED headlights, tail/brake lights

## CAPABILITY

Front Suspension / Wheel Travel	MacPherson Strut/3.1 in
Rear Suspension / Wheel Travel	Unit Swingarm/3.1 in
Front Tires	26x9.00-12
Rear Tires	26x9.00-12
Park Brake Type	Independent, Mechanical Drum
Steering	Rack-and-pinion
Front Brakes	Drum
Rear Brakes	Drum

## DETAILS

Overall Length	106.7 in
Overall Width	52.6 in
Overall Height	75.0 in
Curb Weight	1098.1 lb*
Wheelbase	70.1 in
Instruments	Fuel gauge, hour meter, oil temp light, parking brake light
Wheel Type	Steel
Color Choices	Metallic Onyx Black
Warranty	Kawasaki Strong 3-Year Limited Warranty
Kawasaki Protection Plus™ (optional)	12, 24 or 36 months

\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.  
 KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2022 Kawasaki Motors Corp., U.S.A.  
 Specifications subject to change. Visit [Kawasaki.com](http://Kawasaki.com) for full product details.