## **MULE SX™**











_	_			_	_
P	n			_	n
$\mathbf{r}$		w	v	•	ĸ

4-stroke, single-cylinder, OHV, air-cooled **Engine** 

Displacement 401cc

**Bore x Stroke** 3.23x2.99 in

**Compression Ratio** 8.3:1

20.6 lb-ft @ 2200 rpm **Maximum Torque** 

**Fuel System** Nikki 6C1026 carburetor

**Transmission** Continuously Variable Transmission (CVT) with (H,N,R)

**Final Drive** 2WD, shaft. Dual mode rear differential with differential

lock

**Engine Braking** No

**Alternator Output** 17 amp

(max)

**Rear Tires** 

**Ground Clearance** 6.1 in **Fuel Capacity** 4.2 gal

**Turning Radius** 10.8 ft

Cargo Bed

**Dimensions (LxWxH)** 

**Cargo Bed Capacity** 399 lb **Load Capacity** 926 lb

**Seating Capacity** 

**Towing Capacity** 1100 lb\*\*

Lighting (2) Halogen headlights, tail/brake lights

35.6 x 40.9 x 9.6 in

## **CAPABILITY**

MacPherson Strut/3.1 in Front Suspension / **Wheel Travel** 

Rear Suspension / Wheel Travel

Unit Swingarm/3.1 in

**Front Tires** 22x9.00-10

**Park Brake Type** Independent, Mechanical Drum

22x11.00-10

Rack-and-pinion Steering

**Front Brakes** Drum **Rear Brakes** Drum

## **DETAILS**

**Overall Length** 106.7 in **Overall Width** 52.6 in **Overall Height** 70.1 in **Curb Weight** 967.6 lb\* Wheelbase 70.1 in

Fuel gauge, hour meter, oil temp light, parking brake light Instruments

**Wheel Type** 

**Color Choices** Timberline Green, Dark Royal Red

Kawasaki Strong 3-Year Limited Warranty Warranty

**Kawasaki Protection** 

Plus™ (optional)

12, 24 or 36 months



