
NINJA® ZX™-10R











POWER

Engine 4-stroke, In-Line Four, DOHC, 16-valve, liquid-

cooled

13.0:1

Displacement 998cc

Bore x Stroke 76.0 x 55.0mm

Compression

Ratio

Fuel System

DFI® w/47mm Mikuni throttle bodies (4) with oval sub-throttles, two injectors per cylinder

Ignition TCBI with digital advance and Sport-Kawasaki

Traction Control (S-KTRC)

Transmission 6-speed, return shift

Final Drive Sealed chain

Electronic Rider

Aids

Electronic Cruise Control, Kawasaki Launch Control Mode (KLCM), Kawasaki Sport TRaction Control (S-KTRC), Kawasaki Engine Braking Control, Kawasaki Quick Shifter (KQS) (upshift & downshift), Kawasaki

Corner Management Function (KCMF)

PERFORMANCE

Front Suspension / Wheel Travel

43mm inverted Balance Free Fork, adjustable stepless rebound and compression damping, spring preload adjustability/4.7 in

Rear Suspension / Wheel Travel

Horizontal back-link with Balance Free gascharged shock, stepless, dual-range (low-/highspeed) compression damping, stepless rebound damping, fully adjustable spring preload/4.5 in Front Tire 120/70 ZR17

Rear Tire 190/55 ZR17

Front Brakes Brembo® dual semi-floating 330mm discs with

dual radial-mounted monobloc 4-piston calipers

Rear Brakes Single 220mm disc with aluminum single-piston

caliper

DETAILS

Protection Plus™

(optional)

Frame Type	Aluminum perimeter
Rake/Trail	25.0°/4.1 in
Overall Length	82.1 in.
Overall Width	29.5 in.
Overall Height	46.7 in.
Ground Clearance	5.3 in.
Seat Height	32.9 in.
Curb Weight	452.0 lb*
Fuel Capacity	4.5 gal
Wheelbase	57.1 in.
Color Choices	Metallic Matte Graphenesteel Gray/Metallic Diablo Black
Warranty	12 Month Limited Warranty
Kawasaki	12, 24, 36 or 48 months

^{*}Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.



