## NINJA® ZX™-10R KRT EDITION









P	N	W	F	R

4-stroke, In-Line Four, DOHC, 16-valve, liquid-**Engine** 

cooled

13.0:1

998cc **Displacement** 

**Bore x Stroke** 76.0 x 55.0mm

Compression

Ratio

**Fuel System** 

DFI® w/47mm Mikuni throttle bodies (4) with oval sub-throttles, two injectors per cylinder

TCBI with digital advance and Sport-Kawasaki Ignition Traction Control (S-KTRC)

**Transmission** 6-speed, return shift

**Final Drive** Sealed chain

**Electronic Rider** 

Aids

Electronic Cruise Control, Kawasaki Launch Control Mode (KLCM), Kawasaki Sport TRaction Control (S-KTRC), Kawasaki Engine Braking Control, Kawasaki Quick Shifter (KQS) (upshift & downshift), Kawasaki Corner Management Function (KCMF)

## **PERFORMANCE**

**Front Suspension** / Wheel Travel

43mm inverted Balance Free Fork, adjustable stepless rebound and compression damping, spring preload adjustability/4.7 in

Rear Suspension / **Wheel Travel** 

Horizontal back-link with Balance Free gascharged shock, stepless, dual-range (low-/highspeed) compression damping, stepless rebound damping, fully adjustable spring preload/4.5 in

**Front Tire** 120/70 ZR17

**Rear Tire** 190/55 ZR17

Brembo® dual semi-floating 330mm discs with **Front Brakes** 

dual radial mounted monobloc 4-piston calipers, (and Kawasaki Intelligent Braking System - KIBS)

**Rear Brakes** Single 220mm disc with aluminium single-piston

caliper, (and Kawasaki Intelligent Braking System -

KIBS)

## **DETAILS**

**Overall Height** 

Kawasaki

**Protection Plus™** (optional)

**Frame Type** Aluminum perimeter

NON ABS: 25.0° /4.1 in / ABS: 25.0° /4.2 in Rake/Trail

**Overall Length** 82.1 in. **Overall Width** 29.5 in.

**Ground Clearance** 5.3 in.

**Seat Height** 32.9 in.

**Curb Weight** NON ABS: 452.0 lb / ABS: 456.4 lb\*

46.7 in.

**Fuel Capacity** 4.5 gal

Wheelbase 57.1 in.

**Color Choices** Lime Green/Ebony

Warranty 12 Month Limited Warranty

12, 24, 36 or 48 months

\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.



