

ALL-NEW 2023

NINJA® ZX™ -4RR KRT EDITION

RYMCO
POWERSPORTS



 LIME GREEN/EBONY



POWER

Engine	4-stroke, In-Line Four, OHC, 16-valve, liquid-cooled
Displacement	399cc
Bore x Stroke	57.0 x 39.1mm
Compression Ratio	12.3:1
Fuel System	DFI® w/ 34mm throttle valves (4)
Ignition	Digital
Transmission	6-speed, manual, return shift
Final Drive	Chain
Electronic Rider Aids	Kawasaki TRaction Control (KTRC) (3-mode), Kawasaki Quick Shifter (KQS) (dual direction)

PERFORMANCE

Front Suspension / Wheel Travel	37mm inverted fork with SFF-BP internals and spring preload adjustability/4.7 in.
Rear Suspension / Wheel Travel	Horizontal Back-link, BFRC lite gas charged shock w/ piggyback reservoir, adjustable compression, rebound and spring preload/4.9 in.
Front Tire	120/70 - 17
Rear Tire	160/60 - 17

Front Brakes	Dual 290mm discs, ABS
Rear Brakes	Single 220mm disc, ABS

DETAILS

Frame Type	Trellis, high-tensile steel
Rake/Trail	23.5° / 3.8 in.
Overall Length	78.4 in.
Overall Width	30.1 in.
Overall Height	43.7 in.
Ground Clearance	5.3 in.
Seat Height	31.5 in.
Curb Weight	414.5 lb*
Fuel Capacity	4.0 gal.
Wheelbase	54.3 in.
Special Features	4.3" Full-Color TFT Instrumentation, Smartphone Connectivity using RIDELOGY THE APP
Color Choices	Lime Green/Ebony
Warranty	12 Month Limited Warranty
Kawasaki Protection Plus™ (optional)	12, 24, 36 or 48 months

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.
 KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2022 Kawasaki Motors Corp., U.S.A.
 Specifications subject to change. Visit Kawasaki.com for full product details.