

2023

# VERSYS® 1000 SE LT+

**RYMCO**  
 POWERSPORTS

  
**Kawasaki**  
 Let the good times roll®


 METALLIC GRAPHITE GRAY/METALLIC DIABLO BLACK/  
 METALLIC FLAT SPARK BLACK


## POWER

<b>Engine</b>	4-stroke, 4-cylinder, DOHC, 16-valve, liquid-cooled
<b>Displacement</b>	1,043cc
<b>Bore x Stroke</b>	77.0 x 56.0mm
<b>Compression Ratio</b>	10.3:1
<b>Fuel System</b>	DFI® with 38mm Keihin ETV throttle bodies (4)
<b>Ignition</b>	TCBI with electronic advance
<b>Transmission</b>	6-speed, return shift, Kawasaki Quick Shifter (KQS)
<b>Final Drive</b>	Sealed chain
<b>Electronic Rider Aids</b>	Kawasaki Electronic Control Suspension (KECS), Integrated riding modes, Kawasaki Quick Shifter (KQS), Electronic cruise control and heated grips
<b>Maximum Torque</b>	75.2 lb-ft

<b>Front Brakes</b>	Dual 310mm petal-style discs with four-piston calipers, KIBS ABS
---------------------	--

<b>Rear Brakes</b>	Single 250mm petal disc with single-piston caliper, KIBS ABS
--------------------	--

## DETAILS

<b>Frame Type</b>	Twin-spar aluminum
<b>Rake/Trail</b>	27.0/4.0 in
<b>Overall Length</b>	89.4 in
<b>Overall Width</b>	37.4 in
<b>Overall Height</b>	58.7 in/60.2 in (windshield down/up)
<b>Ground Clearance</b>	5.9 in
<b>Seat Height</b>	33.1 in
<b>Curb Weight</b>	566.7 lb (+ Saddlebags, Hand Guards, & Hardware approx. 20 lb.)*
<b>Fuel Capacity</b>	5.5 gal
<b>Wheelbase</b>	59.8 in
<b>Special Features</b>	All-LED lighting including cornering lights, Multi-function TFT color LCD screen, Smartphone connectivity
<b>Color Choices</b>	Metallic Graphite Gray/Metallic Diablo Black/Metallic Flat Spark Black
<b>Warranty</b>	24 month limited warranty
<b>Kawasaki Protection Plus™ (optional)</b>	12, 24, 36 or 48 months

## PERFORMANCE

<b>Front Suspension / Wheel Travel</b>	43mm inverted fork with KECS-controlled rebound and compression damping, manual spring preload adjustability and top-out springs/5.9 in
<b>Rear Suspension / Wheel Travel</b>	Horizontal back-link New Uni-Trak®, BFRC gas charged shock with piggyback reservoir, KECS-controlled compression and rebound damping electronically-adjustable spring preload/5.9 in
<b>Front Tire</b>	120/70 ZR-17
<b>Rear Tire</b>	180/55 ZR-17

\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.  
 KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2022 Kawasaki Motors Corp., U.S.A.  
 Specifications subject to change. Visit [Kawasaki.com](http://Kawasaki.com) for full product details.

