VULCAN® 900 CUSTOM











ום	n	M	П	С	D
Ε.	U	W		L	N

Engine 4-stroke, 55-degree V-twin, liquid-cooled

Displacement 903cc/55.10 cu in

Bore x Stroke 88.0 x 74.2mm

Compression

Ratio

9.5:1

DFI 34mm Throttle Bodies (2), with sub-throttle **Fuel System**

valves

TCBI w/ Electronic Advance Ignition

Transmission 5-speed with positive neutral finder

Final Drive Kevlar-reinforced belt

Maximum 58.2 lb-ft @ 3500 rpm

Torque

Front

180/70-15

Front Brakes

Rear Tire

Single 300mm hydraulic disc

Rear Brakes

Single 270mm hydraulic disc

DETAILS

Frame Type Semi-double cradle, high-tensile steel

33/7.2 in Rake/Trail

Overall Length 94.7 in

Overall Width 35.2 in

Overall Height 44.1 in

Ground 5.5 in

Clearance

27.0in **Seat Height**

Curb Weight 610.8 lb*

Fuel Capacity 5.3 gal

Wheelbase 64.8 in

Color Choices

Pearl Matte Sage Green/Flat Ebony

Warranty

12 Month Limited Warranty

Kawasaki **Protection**

Plus™ (optional)

12, 24, 36 or 48 months

Rear Suspension / Wheel Travel

Suspension / **Wheel Travel**

> Uni-Trak® swingarm, 7-way adjustable spring preload/4.1 in

41mm Showa telescopic fork/5.9 in

Front Tire 80/90-21

PERFORMANCE

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.



