# **UPDATED 2023**

## **Z650**









METALLIC MATTE GRAPHENESTEEL GRAY/EBONY



METALLIC SPARK BLACK/METALLIC FLAT SPARK BLACK



D	N	W	M	Г	D
Г	u	ľ	V	C	π

4-stroke, 2-cylinder, DOHC, liquid-cooled **Engine** 

**Displacement** 649cc

83.0 x 60.0mm

**Bore x Stroke** Compression

Ratio

10.8:1

DFI® with Keihin 36mm throttle bodies **Fuel System** 

Ignition TCBI with electronic advance

**Transmission** 6-speed, return shift

**Final Drive** Sealed chain

**Electronic Rider** 

Aids

Kawasaki TRaction Control (KTRC - 2 Modes)

**Maximum Torque** 48.5 lb-ft @ 6,500 rpm

## **Front Brakes**

Dual 300mm petal-style discs with two-piston

calipers (and ABS)

**Rear Brakes** 

Single 220mm petal-style disc (and ABS)

#### **DETAILS**

Trellis, high tensile steel **Frame Type** 

Rake/Trail 24.0°/3.9 in

**Overall Length** 80.9 in

**Overall Width** 30.1 in

**Overall Height** 41.9 in

Ground Clearance

(optional)

5.1 in

**Seat Height** 31.1 in

**Curb Weight** NON ABS: 410.1 lb / ABS: 412.3 lb\*

**Fuel Capacity** 4.0 gal

Wheelbase 55.5 in

**Special Features** Rideology the App Smartphone Connectivity, TFT

Instrumentation

**Color Choices** Metallic Spark Black/Metallic Flat Spark Black,

Metallic Matte Graphenesteel Gray/Ebony

Warranty 12 Month Limited Warranty

Kawasaki 12, 24, 26 or 48 months **Protection Plus™** 

### **PERFORMANCE**

Front Suspension / Wheel Travel	Telescopic fork/4.9 in
Rear Suspension / Wheel Travel	Horizontal back-link with adjustable preload, swingarm/5.1 in
Front Tire	120/70 ZR17
Rear Tire	160/60 ZR17

<sup>\*</sup>Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

