









D	N	V	V	E	D
Г	u	v	v	C	π

Engine 4-stroke, 2-cylinder, DOHC, liquid-cooled

Displacement 649cc

Bore x Stroke 83.0 x 60.0mm

Compression

Ratio

10.8:1

Fuel System DFI® with Keihin 36mm throttle bodies

Ignition TCBI with electronic advance

Transmission 6-speed, return shift

Final Drive Sealed chain

Maximum Torque 48.5 lb-ft @ 6,500 rpm

PERFORMANCE

Front Suspension / Wheel Travel	Telescopic fork/4.9 in	
Rear Suspension / Wheel Travel	Horizontal back-link with adjustable preload, swingarm/5.1 in	
Front Tire	120/70 ZR17	
Rear Tire	160/60 ZR17	

Front Brakes	Dual 300mm petal-style discs with two-piston calipers, ABS
Rear Brakes	Single 220mm petal-style disc, ABS

DETAILS

Frame Type	Trellis, high tensile steel
Rake/Trail	24.0°/3.9 in
Overall Length	81.3 in
Overall Width	31.5 in.
Overall Height	43.9 in
Ground Clearance	4.9 in
Seat Height	31.5 in
Curb Weight	412.3 lb*
Fuel Capacity	3.2 gal
Wheelbase	55.3 in
Color Choices	Metallic Moondust Gray/Ebony
Warranty	12 Month Limited Warranty
Kawasaki Protection Plus™ (optional)	12, 24, 26 or 48 months

^{*}Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.



